

# Conventional Sounder Base Beacon CSBB-E



## Features

- ▶ Robust design
- ▶ Low current consumption
- ▶ Easy to install
- ▶ Maximum 93 dB(A) @ 1 metre (Tone 1)
- ▶ 32 user-selectable tones and 3 user-selectable volumes
- ▶ Utilises high intensity LEDs
- ▶ Lockable cap available

## Description

The CSBB-E is platform type sounder beacon, which will accept the CDX Range of detectors mounted with an appropriate base\*. The improved electronics result in a very low current consumption with a high sound output. A set of DIL switches are used to select the unit's tone and sound output (three settings, LOW, MEDIUM and HIGH). Advanced LED technology provides a high intensity flash.

Specification			
Ordering Codes	CSSB-E		
	CSBB-E(WHT)		
	CS/CAP Lockable Cap		
Sound Level	LOW	MEDIUM	HIGH
Sound Output @ 1 metre Tone 1	87 dB(A)	90 dB(A)	93 dB(A)
Current Consumption @ 24Vd.c.	8	9.3	11.5
Voltage Range	18 – 30 VDC		
Number of Tones	32		
Operating Frequency	440 Hz – 2900 Hz		
IP Rating	IP42		
Operating Temperature Range	-20 °C to +70 °C		
Compatible CDX Detectors	SLR-E3N, DCD-AE3, DCD-CE3, DFJ-AE3, DFJ-CE3		
Compatible CDX Bases*	YBN-R/6, YBO-R/6PA, YBO-R/6R, YBO-R/6RN, YBO-R/6RS, YBN-R/6SK		
Colour	Ivory or White		
Weight (g) / Dimensions (mm)	110 / 116 diameter x 25 height		

Hochiki Europe (UK) Ltd. reserves the right to alter the specification of its products from time to time without notice. Although every effort has been made to ensure the accuracy of the information contained in this document it is not warranted or represented by Hochiki Europe (UK) Ltd. to be a complete and up-to-date description.